

# ADITYA SERIES


WS-250 to WS- 295 (60 Cells)

# WAAREE®


One with the Sun



Superior module efficiency as per international benchmarks



1500 VDC system voltage for lower BoS cost



Glass with anti reflective coating improves light transmission



Salt mist, blowing sand and hail resistant




PID resistant with long term reliability




Sustain heavy wind & snow loads (2400 pa & 5400 pa)




Modules binned by current to improve system performance



## I-V VARIATION WITH IRRADIANCE



## I-V VARIATION WITH TEMPERATURE



The Graphs are for reference purpose only. Please consult Waaree technical team for further clarifications.

## INTERNATIONAL & NATIONAL CERTIFICATIONS

IEC 61215:2016 | IEC 61730 1&2:2016 | IEC 61215 ed2 | IEC 61853 | IEC 62782  
IEC 61701 | IEC.TS 62804-1 | IEC 62716 | IEC 60068-2-68 | UL 61730 | IS 14286



ISO 9001:2015 | ISO 14001:2015 | ISO 45001:2018  
Independent assessment of factories by BLACK & VEATCH

# ADITYA SERIES

WS-250 to WS- 295 (60 Cells)

**WAAREE**<sup>®</sup>

One with the Sun

## ELECTRICAL CHARACTERISTICS

Models	Pmax (W)		Vmp (V)		Imp (A)		Isc (A)		Voc (V)		Module Eff. (%)
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	
WS-250	250	185.3	31.15	27.72	8.05	6.68	8.90	7.21	37.10	34.11	15.40
WS-255	255	188.6	31.30	27.91	8.15	6.76	9.00	7.28	37.50	34.48	15.71
WS-260	260	192.1	31.35	28.08	8.30	6.84	9.10	7.36	37.80	34.77	16.01
WS-265	265	195.6	31.45	28.33	8.45	6.90	9.15	7.40	37.90	34.85	16.32
WS-270	270	198.6	31.60	28.53	8.55	6.96	9.20	7.45	38.00	34.93	16.63
WS-275	275	201.8	31.80	28.77	8.65	7.01	9.25	7.48	38.15	35.05	16.94
WS-280	280	205.3	32.00	28.94	8.75	7.09	9.35	7.57	38.30	35.17	17.25
WS-285	285	209.2	32.25	29.18	8.85	7.17	9.45	7.64	38.60	35.45	17.55
WS-290	290	212.9	32.45	29.39	8.95	7.24	9.55	7.73	38.90	35.73	17.86
WS-295	295	216.2	32.60	29.57	9.05	7.31	9.65	7.80	39.20	36.00	18.17

\*Standard Test Conditions (STC) - 1000 W/m<sup>2</sup> irradiance, Air Mass 1.5 and 25°C cell temperature. Nominal Operating Cell Temperature (NOCT) - 800 W/m<sup>2</sup> irradiance, Air Mass 1.5, Ambient temperature 20°C and Wind speed 1 m/s. Average power reduction of 4.5% at 200 W/m<sup>2</sup> as per IEC 60904-1. Measuring Uncertainty ± 3%.


System Voltage	1500 V
----------------	--------

Series Fuse Rating	16 A
--------------------	------

## MECHANICAL CHARACTERISTICS

Length x Width x Thickness (L x W x T)	1640 mm (L) x 990 mm (W) x 40 mm (T)
Weight	18.5 kgs
Solar Cells per Module (Units) / Arrangement	60 / (10x6)
Solar Cell Type & Size	Poly crystalline Silicon, 157 x 157 mm
Front Glass	3.2 mm Low Iron and Tempered glass with ARC coating
Encapsulate	PID Free & UV Resistant
Junction Box (Protection degree / Material)	IP68 / Weatherproof PPO
Connector (Protection degree / Type)	IP68 rated / MC4 compatible
Cable Cross - Section & Length	4 mm <sup>2</sup> & 1200mm

## DESIGN SPECIFICATIONS



## THERMAL CHARACTERISTICS

Temperature coefficient of Current (Isc), $\alpha$ (%/°C)	0.051
Temperature coefficient of Voltage (Voc), $\beta$ (%/°C)	-0.2775
Temperature coefficient of Power (Pm), $\gamma$ (%/°C)	-0.3859
NOCT (°C)	46 ± 2
Operating temperature range (°C)	-40 to 85

Waaree Energies Ltd. is amongst the top Solar Energy Companies and has the country's largest Solar PV Module manufacturing capacity of 2 GW. In addition, it is committed to provide top notch EPC services, project development, rooftop solutions, solar water pumps and also in an Independent Power Producer. Waaree has its presence in over 325+ locations nationally and 68 countries globally.

**10 Years Product Warranty\*** • **25 Years Power Output Warranty\*\***

Minimum 90% at the end of 10 years • Minimum 80% at the end of 25 years

\*If you need specific product certificates, and if module installations are to deviate from our guidance specified in our installation manual, please contact your local Waaree sales and technical representatives.

- The electrical data given here is for reference purpose only.
- Please confirm your exact requirements with the sales representative while placing your order.
- Refer installation Manual instructions & Waaree warranty statement for terms & conditions.
- Waaree Reserves the right to change the specifications without prior notice.

[www.waaree.com](http://www.waaree.com)